



Ultra•Strip III Sheet Label

The Ultra•Strip III Sheet Label provides premier performance and merchandise protection. The sheet format is intended for in-store hand application.

Retailer Values

- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest in detection performance
- // Small label footprint minimizes impact on brand promotion and important product information
- // Reactivable for unlimited reuse
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

Product Codes

- ZLDRS1: White
- ZLDRS2: Mock Barcode
- ZLDRS5: Black

Technology

AM

Environmental Constraints

Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH.

Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

Shelf Life

Two years from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80% RH.

Product Compatibility

Sensormatic AM detection and deactivation devices.

Mode of Application

Hand

Materials of Construction

Plastic Substrate

Polystyrene/Polyethylene 0.3mm (0.012in) thickness

Magnetic Acoustic Resonator

Proprietary resonant magnetic material

Amorphous alloy based on iron, containing nickel, cobalt, boron and silicon

Laminate

Low Density Polyethylene/Polyester
0.119mm (0.0047in)

Bias

Proprietary semi-hard magnetic material containing iron and nickel

Adhesive

Double-coated, rubber-based adhesive:

- // 2.4 mil thick each side
- // Minimum peel strength of 2.27kg/5lbs

Release Liner

Double-sided, silicon-coated 2 mil polyester

Dimensions

ColorWhite, Mock Barcode, Black

Length.....45.21mm ± 0.5mm
(1.78in ± 0.020in)

Width 10.67mm ± 0.5mm
(0.420in ± 0.020in)

Label Thickness

(excluding liner)..... Maximum
1.89mm (0.074in)

(including liner)..... Maximum
2.00mm (0.079in)

Labels Per Sheet 108

* Visit sensormatic.com to download usage guidelines